

35.000 - 110.000 l/h Discs, cartridges, bags

Typical applications




Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive or mechanical seal pump
- Filterchamber with welded bottom (no seal)
- Thin discs (large filter area) or thick discs (large dirt holding capacity)
- Filter paper (thin/thick), cloth, cartridges or bags
- Discs can be removed in manageable stacks
- All PP construction, max. temperature 80°C
- Wheels for portability may be removed once installed
- Multifunctional large round slurry tank with sloping bottom
- Unions for rigid piping (PP, CPVC sockets)
- Standard with 3 phase motor, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection, dry run protection, contact manometer
- Flanges
- Viton




Filter Systems series 36

www.hendor.com


Pump	l/h	kW	Union (d/DN) In Out	Type	Chamber	Medium	Slurrytank	Material
Magnetic drive	35000	3,0	90/75 90/75	MX410		K P Ph B	Option	PP-EPDM
	42000	4,0		108 liter				
Mechanical seal	38000	3,0	90/75 90/75	SB140		K P Ph B	108 liter	PP-EPDM
	46000	5,5		SB150				
	55000	7,5		SB160				

Selection: M4X10 362A P S PP

K = cartridges



P = discs



B = bags

