



F-3-ZB2-SS

## Cartridges, Bag

### Typical applications

Plating and process industry \*)

### Features

- Light weight SS316 filter chamber
- Easy to use Vee clamp closure
- Max. temperature 110°C
- Max. pressure 10 bar
- EPDM O-rings

### Options

- Multiple bag chambers
- Viton O-rings





F-52-HK-SS



F-7-HB2-SS

\*) The housings are suitable for all liquids classified as Group2  
This fluid group is as defined in the European Pressure Equipment Directive 97/23/EC

## Filter chambers in SS316

Type	Qty x L	In / Out	Drain	Vent	Bar	Weight (kg)	Medium
F-31H-K-SS	3 x 10"					11	
F-32H-K-SS	3 x 20"	2"	1/2" x 2	1/4"	10	14	
F-51H-K-SS	5 x 10"					15	
F-52H-K-SS	5 x 20"					18	
Type	OD x L (mm)	In / Out	Drain	Vent	Bar	Weight (kg)	Medium
F-3Z-B2-SS	4" x 400	1 1/2"	NA	1/4"	8,5	5	
F-7H-B1-SS	7" x 430	2"	1/2" (1x)	1/4"	10	15	
F-7H-B2-SS	7" x 860	2"	1/2" (1x)	1/4"	10	21	